



BRULIN SD 1291

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations
Issue date: 11/22/2021 Revision date: 9/29/2023 Supersedes: 11/22/2021 Version: 1.2

SECTION 1: Identification

1.1. Identification

Product form : Mixture
Product name : BRULIN SD 1291
Product code : 304012

1.2. Recommended use and restrictions on use

Recommended use : Solvent, Degreaser
Restrictions on use : None known

1.3. Supplier

Brulin
P.O. Box 270
Indianapolis, IN 46206 - USA
T 1.800.776.7149 / +1.317.923.3211 - F 317.925.4596
Regulatory@brulin.com - www.brulin.com

1.4. Emergency telephone number

Emergency number : CHEMTREC: 1.800.424.9300 or CHEMTREC (International) 1.703.527.3887

SECTION 2: Hazard(s) identification

2.1. Classification of the substance or mixture

GHS US classification

Flammable liquids Category 4 H227 Combustible liquid
Full text of H statements : see section 16

2.2. GHS Label elements, including precautionary statements

GHS US labeling

Signal word (GHS US) : Warning
Hazard statements (GHS US) : H227 - Combustible liquid
Precautionary statements (GHS US) : P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P280 - Wear eye protection.
P370+P378 - In case of fire: Use carbon dioxide (CO₂), dry extinguishing powder, alcohol resistant foam, Water fog to extinguish.
P403+P235 - Store in a well-ventilated place. Keep cool.
P501 - Dispose of contents/container to an approved waste disposal plant.

2.3. Other hazards which do not result in classification

Other hazards which do not result in classification : None known.

2.4. Unknown acute toxicity (GHS US)

Not applicable

BRULIN SD 1291

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 3: Composition/Information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%
dipropylene glycol monomethyl ether	CAS-No.: 34590-94-8	70 – 80

Full text of hazard classes and H-statements : see section 16

SECTION 4: First-aid measures

4.1. Description of first aid measures

First-aid measures after inhalation	: Remove person to fresh air and keep comfortable for breathing.
First-aid measures after skin contact	: Wash skin with plenty of water.
First-aid measures after eye contact	: Rinse eyes with water as a precaution.
First-aid measures after ingestion	: Call a poison center/doctor/physician if you feel unwell.

4.2. Most important symptoms and effects (acute and delayed)

Symptoms/effects	: Not expected to present a significant hazard under anticipated conditions of normal use.
Symptoms/effects after inhalation	: No adverse effects expected.
Symptoms/effects after skin contact	: No adverse effects expected.
Symptoms/effects after eye contact	: May cause slight temporary irritation.
Symptoms/effects after ingestion	: Not expected to present a significant ingestion hazard under anticipated conditions of normal use.
Chronic symptoms	: None known.

4.3. Immediate medical attention and special treatment, if necessary

Treat symptomatically.

SECTION 5: Fire-fighting measures

5.1. Suitable (and unsuitable) extinguishing media

Suitable extinguishing media	: Water spray. Dry powder. Alcohol-resistant foam. Carbon dioxide.
Unsuitable extinguishing media	: Do not use a water jet since it may cause the fire to spread.

5.2. Specific hazards arising from the chemical

Fire hazard	: Combustible liquid. Under fire conditions closed containers may rupture or explode.
Hazardous decomposition products in case of fire	: Toxic fumes may be released.

5.3. Special protective equipment and precautions for fire-fighters

Firefighting instructions	: Use water spray or fog for cooling exposed containers.
Protection during firefighting	: Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

BRULIN SD 1291

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

Emergency procedures : Evacuate unnecessary personnel. Ventilate spillage area. No open flames, no sparks, and no smoking. Do not touch or walk on the spilled product.

6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

For containment : Stop leak, if possible without risk. Collect spillage.
Methods for cleaning up : Take up liquid spill into absorbent material. Notify authorities if product enters sewers or public waters.
Other information : Dispose of materials or solid residues at an authorized site.

6.4. Reference to other sections

For further information refer to section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Ensure good ventilation of the work station. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Wear personal protective equipment.
Hygiene measures : Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Store in a well-ventilated place. Keep cool. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

BRULIN SD 1291	
No additional information available	
dipropylene glycol monomethyl ether (34590-94-8)	
USA - ACGIH - Occupational Exposure Limits	
Local name	(2-Methoxymethylethoxy)propanol
ACGIH OEL TWA [ppm]	100 ppm
ACGIH OEL STEL [ppm]	150 ppm
Remark (ACGIH)	TLV® Basis: Eye & URT irr; CNS impair. Notations: Skin
Regulatory reference	ACGIH 2021

BRULIN SD 1291

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

dipropylene glycol monomethyl ether (34590-94-8)

USA - OSHA - Occupational Exposure Limits

Local name	Dipropylene glycol methyl ether
OSHA PEL (TWA) [1]	600 mg/m ³
OSHA PEL (TWA) [2]	100 ppm
Regulatory reference (US-OSHA)	OSHA Annotated Table Z-1

8.2. Appropriate engineering controls

Appropriate engineering controls	: Ensure good ventilation of the work station. Ensure exposure is below occupational exposure limits (where available).
Environmental exposure controls	: Avoid release to the environment.

8.3. Individual protection measures/Personal protective equipment

Hand protection:

In case of repeated or prolonged contact wear gloves

Eye protection:

If a risk assessment indicates this is necessary, safety glasses are recommended.

Skin and body protection:

Wear suitable protective clothing

Respiratory protection:

If exposure limits are exceeded, NIOSH approved respiratory protection should be worn.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Appearance	: Colorless liquid. clear.
Color	: Colorless
Odor	: Sweet Pungent
Odor threshold	: No data available
pH	: No data available
Melting point	: Not applicable
Freezing point	: No data available
Boiling point	: 100 – 176.67 °C (212 - 350 °F)
Flash point	: 68.3 °C (155 °F)
Relative evaporation rate (butyl acetate=1)	: < 0.1
Flammability (solid, gas)	: Not applicable.
Vapor pressure	: 0.4 mm Hg
Relative vapor density at 20°C	: 5.11
Relative density	: 0.95
Solubility	: Water: 15 - 20 %
Partition coefficient n-octanol/water (Log Pow)	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
Explosion limits	: No data available

BRULIN SD 1291

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Explosive properties : Product is not explosive.
Oxidizing properties : Non oxidizing material.

9.2. Other information

VOC content : 100 %

SECTION 10: Stability and reactivity

10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

Avoid contact with hot surfaces. Heat. No flames, no sparks. Eliminate all sources of ignition.

10.5. Incompatible materials

Strong oxidizing agents.

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral) : Not classified
Acute toxicity (dermal) : Not classified
Acute toxicity (inhalation) : Not classified

dipropylene glycol monomethyl ether (34590-94-8)

LD50 oral rat	> 5000 mg/kg (Equivalent or similar to OECD 401, Rat, Male / female, Experimental value, Oral, 14 day(s))
LD50 dermal rabbit	9510 mg/kg body weight (Equivalent or similar to OECD 402, 24 h, Rabbit, Male, Experimental value, Dermal, 14 day(s))

Skin corrosion/irritation : Not classified
Serious eye damage/irritation : Not classified
Respiratory or skin sensitization : Not classified
Germ cell mutagenicity : Not classified
Carcinogenicity : Not classified
Reproductive toxicity : Not classified
STOT-single exposure : Not classified
STOT-repeated exposure : Not classified
Aspiration hazard : Not classified
Viscosity, kinematic : No data available
Symptoms/effects : Not expected to present a significant hazard under anticipated conditions of normal use.
Symptoms/effects after inhalation : No adverse effects expected.
Symptoms/effects after skin contact : No adverse effects expected.

BRULIN SD 1291

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Symptoms/effects after eye contact	: May cause slight temporary irritation.
Symptoms/effects after ingestion	: Not expected to present a significant ingestion hazard under anticipated conditions of normal use.
Chronic symptoms	: None known.

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general	: The product is not considered harmful to aquatic organisms or to cause long-term adverse effects in the environment.
-------------------	--

dipropylene glycol monomethyl ether (34590-94-8)	
LC50 - Fish [1]	> 1000 mg/l (OECD 203: Fish, Acute Toxicity Test, 96 h, Poecilia reticulata, Static system, Fresh water, Experimental value, GLP)
ErC50 algae	> 969 mg/l (OECD 201: Alga, Growth Inhibition Test, 72 h, Pseudokirchneriella subcapitata, Static system, Fresh water, Experimental value, GLP)

12.2. Persistence and degradability

dipropylene glycol monomethyl ether (34590-94-8)	
Persistence and degradability	Readily biodegradable in water.
Biochemical oxygen demand (BOD)	0 g O ₂ /g substance
ThOD	2.06 g O ₂ /g substance

12.3. Bioaccumulative potential

dipropylene glycol monomethyl ether (34590-94-8)	
Partition coefficient n-octanol/water (Log Pow)	0.004 (Experimental value, OECD 107: Partition Coefficient (n-octanol/water): Shake Flask Method, 25 °C)
Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4).

12.4. Mobility in soil

dipropylene glycol monomethyl ether (34590-94-8)	
Surface tension	68.7 mN/m (20 °C, 1 g/l, OECD 115: Surface Tension of Aqueous Solutions)
Partition coefficient n-octanol/water (Log Koc)	1 (log Koc, SRC PCKOCWIN v2.0, Calculated value)
Ecology - soil	Highly mobile in soil.

12.5. Other adverse effects

No additional information available

SECTION 13: Disposal considerations

13.1. Disposal methods

Waste treatment methods	: Dispose of contents/container in accordance with licensed collector's sorting instructions.
-------------------------	---

BRULIN SD 1291

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 14: Transport information

In accordance with Department of Transport / IMDG / IATA

DOT	IMDG	IATA
14.1. UN number		
NA1993	Not applicable	Not applicable
14.2. Proper Shipping Name		
Combustible liquid, n.o.s. (CONTAINS : dipropylene glycol monomethyl ether)	Not applicable	Not applicable
14.3. Transport hazard class(es)		
Combustible liquid	Not applicable	Not applicable
14.4. Packing group		
III	Not applicable	Not applicable
14.5. Environmental hazards		
Dangerous for the environment: No	Not applicable	Not applicable
No supplementary information available		

14.6. Special precautions for user

DOT

DOT NA No	: NA1993
DOT Special Provisions (49 CFR 172.102)	: 148 - For domestic transportation, this entry directs to § 173.66 for: a. The standards for transporting a single bulk hazardous material for blasting by cargo tank motor vehicles (CTMV); and b. The standards for CTMVs capable of transporting multiple hazardous materials for blasting in bulk and non-bulk packagings (i.e, a multipurpose bulk truck (MBT)). IB3 - Authorized IBCs: Metal (31A, 31B and 31N); Rigid plastics (31H1 and 31H2); Composite (31HZ1 and 31HA2, 31HB2, 31HN2, 31HD2 and 31HH2). Additional Requirement: Only liquids with a vapor pressure less than or equal to 110 kPa at 50 C (1.1 bar at 122 F), or 130 kPa at 55 C (1.3 bar at 131 F) are authorized, except for UN2672 (also see Special Provision IP8 in Table 2 for UN2672). T1 - 1.5 178.274(d)(2) Normal..... 178.275(d)(2) TP1 - The maximum degree of filling must not exceed the degree of filling determined by the following: Degree of filling = $97 / 1 + a (tr - tf)$ Where: tr is the maximum mean bulk temperature during transport, and tf is the temperature in degrees celsius of the liquid during filling.
DOT Packaging Exceptions (49 CFR 173.xxx)	: 150
DOT Packaging Non Bulk (49 CFR 173.xxx)	: 203
DOT Packaging Bulk (49 CFR 173.xxx)	: 241
DOT Quantity Limitations Passenger aircraft/rail (49 CFR 173.27)	: 60 L
DOT Quantity Limitations Cargo aircraft only (49 CFR 175.75)	: 220 L
DOT Vessel Stowage Location	: A - The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel.

IMDG

No data available

IATA

No data available

BRULIN SD 1291

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable

SECTION 15: Regulatory information

15.1. US Federal regulations

BRULIN SD 1291

SARA Section 311/312 Hazard Classes

Refer to Section 2 for the OSHA Hazard Classification.

All components of this product are present and listed as Active on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory

This product or mixture is not known to contain a toxic chemical or chemicals in excess of the applicable de minimis concentration as specified in 40 CFR §372.38(a) subject to the reporting requirements of section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372.

15.2. International regulations

CANADA

BRULIN SD 1291

Listed on the Canadian DSL (Domestic Substances List)

dipropylene glycol monomethyl ether (34590-94-8)

Listed on the Canadian DSL (Domestic Substances List)

EU-Regulations

No additional information available

National regulations

BRULIN SD 1291

Listed on NZIoC (New Zealand Inventory of Chemicals)
Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances)
Listed on KECL/KECI (Korean Existing Chemicals Inventory)
Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China)
Listed introduction on Australian Industrial Chemicals Introduction Scheme (AICIS Inventory)
Listed on the Japanese ENCS (Existing New Chemical Substances) inventory

15.3. US State regulations

WARNING:

This product can expose you to formaldehyde, which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov.

Component	State or local regulations
dipropylene glycol monomethyl ether(34590-94-8)	U.S. - New Jersey - Right to Know Hazardous Substance List; U.S. - Pennsylvania - RTK (Right to Know) List

BRULIN SD 1291

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 16: Other information

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Revision date : 09/29/2023

Full text of H-phrases	
H227	Combustible liquid

Safety Data Sheet (SDS), USA

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.